SAFETY ORGANIZATIONS

THIS FILTER HAS BEEN FORMALLY RECOGNIZED, CERTIFIED OR APPROVED BY THE LISTED AGENCY. THEREFORE, ALL TEST/REQUIREMENTS SPECIFIED IN THE LATEST REVISION OF THE FOLLOWING AGENCY STANDARDS HAVE BEEN MET:

UL RECOGNIZED: UL 60939-3

OPERATING SPECIFICATIONS

LINE CURRENT/VOLTAGE: 2.0 AMP/90°C, 480 VAC 50-60Hz 2.0 AMP/90°C, 480 VDC

MAXIMUM LEAKAGE CURRENT,

EACH LINE TO GROUND: 0.28 mA @ 277V 60Hz 0.21 mA @ 250V 50Hz

OPERATING AMBIENT TEMP. RANGE: -40°C TO +90°C @ RATED CURRENT, In. IN AN AMBIENT, T_0 , HIGHER THAN 90°C, THE MAXIMUM OPERATING CURRENT, I_0 , IS AS FOLLOWS: $I_1 = I_1 - I_2 - I_3 = I_4 - I_4 - I_5 = I_5 - I_6 = I_6 - I_6 - I_6 = I_6 - I$

100 - Ta $I_0 = I_r \neg$ 10

RELIABILITY SPECIFICATIONS:

STORAGE TEMPERATURE: -40°C TO +100°C HUMIDITY: 21 DAYS @ 40°C 95% RH.
CURRENT OVERLOAD TEST: 6 TIMES I PFOR 8 SECONDS

CUSTOMER DRAWING CATALOG # 2FBH3 ECN# APPRVD DATE

TEST SPECIFICATIONS:

INDUCTANCE: 0.51 mH NOMINAL

 $0.51~\mathrm{mH}$ NOMINAL

CAPACITANCE: (MEASURED @ 1 kHz, 0.250VAC MAX., 25°C±1°C)

LINE TO GROUND: 0.0044uF ± 20 % LINE TO LINE: 0.011uF ± 20 % DISCHARGE RESISTOR: 20 MEGOHM

L/G AND L/L I.R.


NO DISCHARGE RESISTOR: 6000MEGOHM (MIN.) 100VDC 20°C AND 50% RH

RECOMMENDED RECEIVING INSPECTION HIPOT:

LINE TO GROUND: 2250 VDC FOR 1 MINUTE LINE TO LINE: 2775 VDC FOR 1 MINUTE

FILTER APPROVAL:

THE BEST WAY TO SELECT AND QUALIFY A FILTER IS FOR YOUR ENGINEERING TO TEST THE UNIT IN YOUR EQUIPMENT.



50 a - 50 a (TYPICAL) INSERTION LOSS													PARTS SHALL COMPLY WITH TYCO ELECTRONIC	S 138-702 SPECIFICATION FOR HAZARDOUS SUBSTANCES
FREQUENCY MHz	.03	.05	.1	.15	.5	1.0	2.0	5.0	10	20	30	/	UNLESS DTHERWISE SPECIFIED TDLERANCE TO BE ±0.025 MATERIAL & FINISH; AS SUPPLIED	TE TE Connectivity
COMMON dB	3	6	11	15	21	24	28	35	40	48	61	/	NOTES:	RFI FILTER
DIFF. dB sheet size	()	O O	O ECTION I	1	5	10	15	18	53	60	78	/		TYCO ELECTRONICS PART NO. 2-1609028-9
A) (5)	THIS INFORMATION IS COMFIDENTIAL AND PROPRIETARY TO TYCO ELECTRONICS CORPORATION AND ITS WORDUNGE SUBSIDIARIES AND AFFILIATES. IT MAY NOT BE DISCLOSED TO ANYONE OTHER THAN TYCO ELECTRONICS PERSONNEL, WITHOUT WRITTEN AUTHORIZATION FROM TYCO ELECTRONICS CORPORATION. HARRISBURG, PENNSTLVANIA USA.							TES. IT	MAY NOT	2FBH3-A.ckd	$\begin{array}{c ccccccccccccccccccccccccccccccccccc$